

## Environmental Protection Agency

## § 98.202

(4) Standard method used (ASTM or NLA testing method) to determine chemical compositions of each lime type produced and each calcined lime byproduct/waste type.

(5) Monthly results of chemical composition analysis of each type of lime product produced and calcined byproduct/waste sold.

(6) Annual results of chemical composition analysis of each type of lime byproduct/waste that is not sold.

(7) Method used to determine the quantity of lime produced and/or lime sold.

(8) Monthly amount of lime product sold, by type (tons).

(9) Method used to determine the quantity of calcined lime byproduct/waste sold.

(10) Monthly amount of calcined lime byproduct/waste sold, by type (tons).

(11) Annual amount of calcined lime byproduct/waste that is not sold, by type (tons).

(12) Monthly weight or mass of each lime type produced (tons).

(13) Beginning and end of year inventories for each lime product that is produced.

(14) Beginning and end of year inventories for calcined lime byproducts/wastes sold.

(15) Annual lime production capacity (tons) per facility.

(16) Number of times in the reporting year that missing data procedures were followed to measure lime production (months) or the chemical composition of lime products sold (months).

(17) Indicate whether CO<sub>2</sub> was used on-site (i.e. for use in a purification process). If CO<sub>2</sub> was used on-site, provide the information in paragraphs (b)(17)(i) and (ii) of this section.

(i) The annual amount of CO<sub>2</sub> captured for use in the on-site process.

(ii) The method used to determine the amount of CO<sub>2</sub> captured.

[75 FR 66465, Oct. 28, 2010]

### § 98.197 Records that must be retained.

In addition to the records required by § 98.3(g), you must retain the records specified in paragraphs (a) and (b) of this section.

(a) Annual operating hours in calendar year.

(b) Records of all analyses (e.g. chemical composition of lime products, by type) and calculations conducted.

### § 98.198 Definitions.

All terms used in this subpart have the same meaning given in the Clean Air Act and subpart A of this part.

TABLE S-1 TO SUBPART S OF PART 98—BASIC PARAMETERS FOR THE CALCULATION OF EMISSION FACTORS FOR LIME PRODUCTION

Variable	Stoichiometric ratio
SR <sub>CaO</sub> .....	0.7848
SR <sub>MgO</sub> .....	1.0918

## Subpart T—Magnesium Production

SOURCE: 75 FR 39761, July 12, 2010, unless otherwise noted.

### § 98.200 Definition of source category.

The magnesium production and processing source category consists of the following processes:

(a) Any process in which magnesium metal is produced through smelting (including electrolytic smelting), refining, or remelting operations.

(b) Any process in which molten magnesium is used in alloying, casting, drawing, extruding, forming, or rolling operations.

### § 98.201 Reporting threshold.

You must report GHG emissions under this subpart if your facility contains a magnesium production process and the facility meets the requirements of either § 98.2(a)(1) or (2).

### § 98.202 GHGs to report.

(a) You must report emissions of the following gases in metric tons per year resulting from their use as cover gases or carrier gases in magnesium production or processing:

- (1) Sulfur hexafluoride (SF<sub>6</sub>).
- (2) HFC-134a.